









The Carinya Select Range includes a variety of windows and doors suitable for all homes.



Products include sliding windows, sliding doors, double hung windows and awning windows.

All can be made single or double glazed.



Classic Range

High Performance Sliding Window

The Carinya Classic
High Performance
Sliding Window is a new
development not previously
available in the residential
category for Australia's
most demanding terrain
requirements.

Besides a modern designer look, the Carinya Classic High Performance Sliding Window is packed with a multitude of performance features, many of which are simply not available in competing products:

- Rather than unsightly exposed tracks found in most residential windows, Carinya has a complete range of threshold and jamb infills as well as end caps to conceal all cavities. This not only provides a superior quality, commercial grade finish but also minimises places for insects, dirt and grit to gather.
- All can be made single or double glazed.
- A range of attractive interlock options to meet a wide variety of wind load requirements.
- Sills to suit the most severe conditions of residential construction.

The entire Carinya Collection has been fully tested to meet or exceed Australian Standards AS2047, AS1170, AS1191 and AS3959











Streamlined Hardware

The Carinya Classic High Performance Sliding Window has been matched with commercially designed hardware to ensure style and durability in the harshest of environments.



58mm wide rails and stile

Our Sliding Window Lock provides functionality and varying finish options for your project. This functional retractable handle design allows for ease of use and utilises 5 pin cylinder security for peace of mind.

To maximise the performance of your sliding window we have utilised our proprietary Alspec roller system used throughout our commercial range.

Stainless rollers and optional stainless cover track are also available for coastal environments, allowing for enduring performance and durability.

Both roller systems have been designed to interact with the stiles to create a strong and robust panel, minimising movement in joints and opportunities for air infiltration.



Commercial grade rollers up to 160kg

Applications

- Region D Residential Construction for Cyclonic Compliance
- Double Glazing without adaptors for a premium option
- Low-Rise Multi-Unit Developments

Specifications


- Maximum Panel Height: 1800mm
- · Maximum Panel Width: 1200mm
- Maximum Single Glazed Thickness: 12mm
- Maximum Double Glazed Thickness: 18mm
- Maximum Sash Weight: 160kg
- Frame width available in 92mm

Options

- A range of sill options available for increased structural, water performance and design flexibility.
- A range of internal interlocks complete with end caps for varying wind load requirements.
- Integral screening options for security or insect protection.

Configurations

Custom Windows can offer the typical standard configurations below, as well as custom options to suit your requirements: All can be made single or double glazed.









Showrooms

67 McDonald Cres, Bassendean WA 6054 Display 62, Homebase Subiaco, 55 Salvado Rd, Subiaco WA 6008 For any more information on any of our products or services, please give us a call today to speak to a member of our team.

We look forward to hearing from you!

(08) **9279 7444** sales@customwindows.com.au